

Elastomer Coupling - Elastomer Insert

- ✓ high quality plastic
- ✓ good resistance
- ✓ low wear
- ✓ high torsional stiffness
- ✓ no electrostatic charge



series	elastomer insert	shore hardness	colour	offset axial (mm)	offset radial (mm)	offset angular (degree)	temperature range
10	A	98 Sh A	orange	+1/-0,5	0,09	0,9	-30°C to +100°C
10	B	64 Sh D	gray	+1/-0,5	0,06	0,8	-20°C to +100°C
30	A	98 Sh A	orange	+1,2/-0,5	0,06	0,9	-30°C to +100°C
30	B	64 Sh D	gray	+1,2/-0,5	0,04	0,8	-20°C to +100°C
60	A	98 Sh A	orange	+1,4/-0,5	0,1	0,9	-30°C to +100°C
60	B	64 Sh D	gray	+1,4/-0,5	0,07	0,8	-20°C to +100°C
150	A	98 Sh A	orange	+1,5/-0,7	0,11	0,9	-30°C to +100°C
150	B	64 Sh D	gray	+1,5/-0,7	0,08	0,8	-20°C to +100°C
300	A	98 Sh A	orange	+1,8/-0,7	0,12	0,9	-30°C to +100°C
300	B	64 Sh D	gray	+1,8/-0,7	0,09	0,8	-20°C to +100°C
							CT-ES-22-01

Values at 20°. Values are generally temperature-dependent.